

CITIE 3000 Standard Series					
Model No.	PL-CT 35W	PL-CT 66W	PL-CT 100W	PL-CT 135W	PL-CT 150W
System Watts	35W±5%	66W±5%	100W±5%	135W±5%	150W±5%
LED Chips	OSRAM / PHILIPS				
CRI	Ra ≥82				
LED nos.	42pcs	84pcs	126pcs	168pcs	
Total Lumens(Cool-White)	≥4,550 lm (≥130 lm/W)	≥8,550 lm (≥130 lm/W)	≥13,000 lm (≥130 lm/W)	≥17,550 lm (≥130 lm/W)	≥19,500 lm (≥130 lm/W)
Drivers	MeanWell HLG series LED Driver, 1~10V Dimmable				
AC Input	90~305V				
Operation Temp.	-40°C~50°C				
Storage Temp.	-40°C~80°C				
IP Rating	IP66				
Beam Angles	135° Semi-Cut Type III				
Color Temp.	Warm White(3000K) / Natural White(4000K) / Cool White(5000K)				
Dimensions	381x246x113mm				
Weight	3.9kg (Driver excluded) 4.8kg (Driver included)				
Material	Die-casting Aluminum Heat Sink, White / Black painting, MCPCB,PC Lens				
Surge Protection	SPD Meets ANSI C136.2 Enhanced Level 10kV/5kA (20kV Optional)				
Warranty	5 Years, LifeSpan>50,000 hrs				
COO	Made in Taiwan				
Passed the Test	Passed 360 hrs salty spray test, >60m/sec wind pressure test (Limit model, please query for detail information.)				
Certification					